

**DESCRIPTION**

New thin, flexible 60W USB-C power supplies provide up to 20V at 3A

**APPLICATION**

Mobile Phones, Tablets, Automotive convenience ports, TV, Mass Storage, Expansion Ports, Laptops, Monitors, Payment terminal, Set-top boxes, Workstations

**FEATURES**

- AC Input 100 to 240v AC, at 2A 47-63 Hz
- Wide range of output voltages, up to 20v at 3A
- Able to power devices up to 60 watts
- The thinnest C14 adapter available today, only 92 x 77.3 x 25.4mm
- Includes ground wire for safety
- High power output density of up to 6.01 W/in<sup>3</sup>
- Meets DoE level 6 standard for energy efficiency
- C14 and C6 AC socket versions available
- Full thermal and electrical safety protection
- Elegant, simple, compact design
- There are five different output voltage (5v, 9v, 12v, 15v, 20v)

**WATTAGE**

Wattage: 60W

**PRODUCT HIGHLIGHT**

V-Output: 5,9,12,15,20  
 O/ P Current: 3A  
 Socket Type: C14

**INPUT ELECTRICAL**

Input Voltage: 100 ~ 240 V  
 Input Frequency: 47 ~ 63 Hz  
 Input Current: 2A

**OUTPUT ELECTRICAL**

Single Output: 5 V/ 3 A  
 Second Output: 9V/ 3A  
 Third Output: 12V/ 3A  
 Fourth Output: 15V/ 3A  
 Output Accuracy: +/- 5%  
 Line Regulation: +/- 5%  
 Load Regulation: +/- 5%



**SAFETY STANDARD APPROVAL**



**NO LOAD AND EFFICIENCY**

No Load: 0.21 Watts  
 Efficiency: 88 %

**PROTECTION**

Protection: OVP, OCP, OTP, OPP

**ENVIRONMENTAL REQUIREMENTS**

MTBF: 300,000Hrs Min. Telcordia SR-332 Issue2 (25°C)

**MECHANICAL**

Dimension: 92mm(L) x 77.3mm(W) x 25.4mm(H)  
 LED Indicator: No  
 On/ Off Switch: No

This content is subject to change, please refer to specification for more detail. FSP reserve the right to change the content without prior notice